

FOR GENERAL REFERENCE ONLY Models shown may not match the model features or manuf year of the item offered by AERE.



Food Service

Bizerba GSP series slicers are certified to the NSF/ANSI Standard 8-2017

Safety is our top-priority ...

... GSP H STD-90 series – manual safety slicer ...

GSP H Standard Safety Features - 90mm wide Thumb Guard

- Energy Efficiency: 1/2 H.P. motor, 319 r.p.m.
- High Yield: Operating time, designed for permanent operation
- High Yield: Unique carriage-shifting design allows for the smallest end pieces, increased product yield
- High Yield: Widest product carriage for increased capacity
- High Yield: Heavy-duty, 3 lb. blade knife cover
- High Yield: Debris deflector, permanently mounted, included
- High Yield: Precision machined pencil-point-groves on gauge plate, blade cover and carriage to reduce friction, better looking product
- Safety Interlock: No-volt release
- Safety Interlock: Adjustable blade shut off settings: 15, 30, 45 seconds or off
- Safety Interlock: Shut off in slice thickness knob
- Safety Interlock: Carriage and gauge plate lock during the cleaning process
- Safety Interlock: Forced start with slice thickness knob below zero
- Operator Safety: Slicer installation, start-up and training, included
- Operator Safety: 3.5"W (90mm) x 9.13"H x 2.6"D thumb guard wall for maximum protection
- Operator Safety: 360° blade enclosure, no top-gaps in blade ring-guard
- Operator Safety: Zero blade exposure during the cleaning process
- Operator Safety: Front mounted controls
- Operator Safety: Rear mounted lift arm with largest and easiest to use remnant holder with 306 holding points, removable for cleaning, dishmachine safe
- Operator Safety: Low profile carriage for easy loading of heavy product
- Operator Safety: Side lift arm for easy cleaning under slicer
- Operator Safety: Recommended 31.25" above floor height
- Food Safety: One piece anodized aluminum construction
- Food Safety: Non-removable carriage system for faster cleaning and sanitizing
- Food Safety: Double-sided seal between blade knife and housing, no gap for food to collect, better hygiene
- Food Safety: UL157 dairy grade seals and gaskets used to seal against water and food debris, no silicone used under seals, better hygiene
- Food Safety: Liquid and debris diversion from all control surfaces
- Food Safety: Remote blade sharpener does not collect food debris during operation and is dishwasher safe for improved safety and hygiene
- Food Safety: One piece carriage with seamless thumb guard for highest hygiene standards, no slotted-screw heads on thumb guard
- One Year Warranty: On-site, labor and parts



Best blade in the industry

The unique design of our blade produces clean and consistent slices. The hardness results in a long lasting sharp edge. The life of the blade is dramatically longer than the competition.

Our standard blade is the hardest, thinnest, largest, straightest blade in the industry.

- 13" diameter, chromium coated hard alloy
- 60-62 Rockwell hardness at the edge









Food Service

1-phase AC current

- 120 V, specialised data available on request
- 60 Hz

Quantity: _

- Frequency of nominal current 3.5 A
- Power consumption 0.360 kW

Blade diameter

13" (330 mm)

Blade speed

■ 319 r.p.m.

Max. produce size

- Height: 4.96" (126 mm)
- Width: 11.6" (290 mm)
- Round: 8" (200 mm)
- Rectangular: 11.6 x 6.4" (290 x 160 mm)

Slice thickness

■ 0-0.94" (0-24 mm), infinitely variable

Thumb-guard rear wall

3.5"W x 11.13"H x 2.6"D (90 x 235 x 67 mm)

Gravity-feed slicing carriage

40° inclined gravity feed

H - Carriage inclination

- Carriage inclined 25° towards operator
- Carriage height positioned towards center of blade

Noise control drive system

58 dB decibel level

Installation area

■ (L x W) 20.94" x 18.82" (530 x 480 mm)

External dimensions

(L x W x H) 28.54" x 23.07" x 23.46" 725 x 586 x 596 mm)

Operating area

(L x W) 31.73" x 35.4" (806 x 899 mm)

Food Safety - Ingress Protection type

IP Solids level 3 | Liquids level 3

Weight of machine

95.1 lbs, 43 kg

Shipping Details & Dimensions

- Total Shipping Dimensions (L x W x H): 32.5" x 27.8" x 32" (826 x 706 x 813 mm)
- Total Shipping Weight: 124 lbs, 56.3 kg
- Cubic: Ft. 16.73, 0.47 m
- Density: 7.41 lb/cubic ft, 118.95 kg/cubic m

Additional equipment

- Equipment Stand
- Extended Warranty
- 13" (330 mm) Grooved Vacuum Release Blade




Remote sharpener, better food safety











Warranty

The GSP H Safety Slicer carries a one-year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins with the date of purchase and, provided the unit is used properly in accordance with our instructions, is in full effect for one year from that date. Any work to be performed under this warranty must be performed between the hours of 8:00 a.m. and 4:30 p.m. local time, Monday to Friday. Bizerba will not pay overtime charges for work performed other than during normal business hours. Accessories have a 30-day replacement or repair warranty for the period beginning on the date of purchase. Damages incurred in transit or from installation error, accident, alteration or misuse are not covered. Transit damages should be reported to the carrier immediately. Bizerba shall not be liable for any consequential, compensatory, incidental, or special damages. All warranty work must be performed by a factory authorized Bizerba Representative.

Members of the Bizerba Group

D 1.77" (45)

L1 19.17" (487)

L 28.54" (725)

L2 31.74" (806)

Bizerba GmbH & Co. KG Wilhelm-Kraut-Straße 65 72336 Balingen Germany Tel. +49 7433 12-0 Fax +49 7433 12-2696

marketing@bizerba.de

www.bizerba.com

1804 Fashion Court Joppa, MD 21085 USA Tel Office +1 732 565-6000 Tel. Service +1 732 565-6001 Fax +1 732 819-0429 us.foodservice@bizerba.com www.bizerba.com

Bizerba USA Inc.

Bizerba Canada Inc. 6411 Edwards Blvd. Mississauga, Ontario L5T2PT Canada Tel +1 888 240-3722

French Tel. +1 877 699-2199 Fax +1 905 816-0497 ca.info@bizerba.com www.bizerba.ca

Bizerba de México, S.A. de C.V. Av. Rio Mixcoac No. 157 Colonia Florida 01030 México, D.F. México Tel. +52 55 5663-1397 Fax +52 55 5663-1296 contacto@bizerba.com.mx

AutoQuotes

www.bizerba.com.mx

