

HEAVY-DUTY SLICERS





Heavy-Duty Slicers

DESCRIPTION

Vollrath's five heavy-duty slicers, all with 12" (30.5 cm) blades and a non-stick coating, are designed to meet the challenges of any high-use operation.

FEATURES

- Exclusive non-stick coating makes for easy clean up after slicing products
- One-piece, light weight, hard-coated anodized aluminum body eliminates food traps
- Sand-molded, anodized aluminum base will never tarnish
- Clearance between the back of the blade and the motor provides access for easy and thorough cleaning
- Receiving tray features raised edges to contain juices which keeps the slicer and work area clean
- Solid aluminum adjustment knob is easy to clean
- Heavy-duty blade guides will not flex, creating straight slices every time
- Precision spacing cam for more accurate thickness cutting
- Built-in easy to use two stone sharpener makes blade sharpening simple and convenient
- Heavy-weight pusher feeds product into the blade for easier cuts and less user fatigue
- Easy-tilt product feeder mechanism makes it easy to clean safely without the product feeder dropping
- Low-friction carriage system provides outstanding smooth glide motion
- Thermal overload protection with manual reset automatically shuts off slicer to protect from electrical damage
- 5 ft. (1.5 m) cord with plug

Agency Listings



Certified to NSF/ANSI 8-2010

WARRANTY: All models shown come with Vollrath's standard warranty against defects in materials and workmanship. For full warranty details, please refer to the Vollrath Equipment and Smallwares Catalog.

MODELS

40903 SLR7012/N Belt Driven (US/Canada)

40904 SLR 7712/N Belt Driven with Safe Blade Removal

System (US/Canada)

Quantity:

40905-QC SLR7012/N Belt Driven (Quebec)
40906 SLR7512/N Gear-Driven (US/Canada)

40907 SLR7912/N Automatic Slicer with Safe Blade Removal

(US/Canada)

40908 SLM0012/N Belt Driven with Maximum Clearance

Receiving Tray and Safe Blade Removal (US/Canada)

FEATURES (CONTINUED)

Belt Driven

- Heavy-duty slice adjustment for precise and consistent slice thickness
- Centered blade and gauge plate ensure stability under the toughest conditions

Gear Driven

 Direct drive gear transmission provides the power and robustness for high-volume slicing of cheese and meat

Maximum Clearance Receiving Tray

- Special clear slice exit design provides unobstructed receiving tray area for easier slicing and cleaning
- Extended 1¼"(3.175 cm) maximum slice thickness for greater versatility

Automatic Carriage

- Automatic carriage slices approximately 40 slices per minute for maximum operational efficiency
- Intuitive setup includes simple main switch and variable speed control
- Can also be used manually

MODEL COMPARISON

Feature	40903	40904	40905-QC	40906	40907	40908
Non-Stick Coating	Х	Х	Х	Х	Х	Х
Accommodates Vegetable Chute	х	Х	х	Х	х	Х
Accommodates Frozen Food Blade	х	Х	Х	Х	х	Х
Safe Blade Removal System	-	Х	-	-	х	Х
Gear Drive	-	-	-	Х	-	-
Belt Drive	Х	Х	Х	-	Х	Х
Kickstand	-	-	-	Х	Х	Х
Max Clearance Receiving Tray	-	-	-	-	-	Х
Automatic Cartridge	-	-	-	-	Х	-

Approvals Date

Due to continued product improvement, please consult www.vollrath.com for current product specifications.



HEAVY-DUTY SLICERS

MODELS

40903 SLR7012/N Belt Driven (US/Canada)

SLR 7712/N Belt Driven with Safe Blade 40904

Removal System (US/Canada)

40905-QC SLR7012/N Belt Driven (Quebec) 40906 SLR7512/N Gear-Driven (US/Canada)

40907 SLR7912/N Automatic Slicer with Safe Blade Removal (US/Canada)


40908 SLM0012/N Belt Driven with Maximum Clearance Receiving Tray and

Safe Blade Removal (US/Canada)


DIMENSIONS


Dimensions shown in inches (cm).

40903 / 40904 / 40905-QC





Front View





40906







Side View

Front View


Side View


40907





40908





Front View

Side View

SPECIFICATIONS

		Slicing Capacity					
Item	Drive	Processed Meats	Cheese	НР	Voltage	Amps	Plug
40903	Belt	3 hr/day	1 hr /day or less	1/2	120	2.5	NEMA 5-15P
40904	Belt	3 hr/day	1 hr /day or less	1/2	120	2.5	NEMA 5-15P
40905-QC	Gear	3 hr/day	1 hr /day or less	1/2	120	2.5	NEMA 5-15P
40906	Gear	Continuous	Continuous	1/2	120	2.5	NEMA 5-15P
40907	Belt	Continuous	Continuous	3/4	120	4.7	NEMA 5-15P
40908	Belt	Continuous	3 hr/day	2/3	120	2.5	NEMA 5-15P

Receptacle





The Vollrath Company, L.L.C. 1236 North 18th Street Sheboygan, WI 53081-3201 U.S.A. Customer Service: 800.628.0830 Canada Customer Service: 800.695.8560

Main Fax: 800.752.5620 or 920.459.6573

Technical Services: 800.628.0832 Technical Services Fax: 920.459.5462